


FLEXADUX® HT 450 CL

Highly flexible clip hose for temperatures up to +450°C

- Applications** exhaust gas extraction, extraction systems, high temperature applications, automotive engineering, automation technology & robotics
- Structure** coated fabrics / high temperature silicone coated glass fabric, grey / silver grey (similar RAL 7001), clip profile / multi-layer
- Temperature** -60°C up to 450°C
- Properties** very good flexibility, excellent temperature resistance, compressible, with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,75	30	0,90	0,44	0,91	04100050
60	0,75	36	0,78	0,31	1,09	04100060
65	0,75	39	0,68	0,26	0,80	53335065
70	0,75	42	0,67	0,23	0,90	53335070
76	0,75	45	0,62	0,20	1,37	04100076
80	0,75	48	0,61	0,17	1,45	04100080
83	0,75	54	0,56	0,14	1,20	53335083
102	0,75	60	0,51	0,11	1,28	04100102
112	0,75	66	0,48	0,09	1,41	04100112
120	0,75	72	0,36	0,08	1,51	04100120
127	0,75	75	0,33	0,07	1,59	04100127
140	0,75	84	0,25	0,06	1,60	53335140
152	0,75	90	0,22	0,05	2,01	04100152
160	0,75	96	0,21	0,04	2,01	04100160
180	0,75	108	0,17	0,04	2,10	53335180
203	0,75	120	0,15	0,03	2,54	04100203
254	0,75	175	0,10	0,02	3,18	04100254
305	0,75	210	0,07	0,01	3,82	04100305
407	0,75	280	0,05	0,01	5,09	04100407
508	0,75	400	0,04	0,01	6,36	04100508