

# FLEXADUX® PTFE CL

Very light weight and highly flexible clip hose made of PTFE

- Applications** paint mist extraction, solvent vapor extraction, high temperature applications, extraction systems, extractions arms
- Structure** coated fabrics / PTFE coated glass fabric, brown, clip profile / single-layer
- Temperature** -150°C up to 250°C
- Properties** light weight, good flexibility, very good temperature resistance, very good chemical resistance, with external abrasion protection spiral
- Optional**
  - electrically conductive ( $R \leq 10^6 \text{ Ohm}$ )
  - with stainless steel clip profile



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,12	30	0,85	0,32	0,38	03380050
60	0,12	36	0,68	0,22	0,45	03380060
76	0,12	45	0,47	0,14	0,57	03380076
80	0,12	48	0,43	0,12	0,60	03380080
102	0,12	60	0,30	0,08	0,53	03380102
110	0,12	66	0,25	0,07	0,57	03380110
120	0,12	72	0,22	0,06	0,62	03380120
127	0,12	75	0,21	0,05	0,66	03380127
152	0,12	90	0,16	0,04	0,78	03380152
160	0,12	96	0,14	0,03	0,83	03380160
180	0,12	108	0,12	0,02	0,93	03380180
203	0,12	120	0,10	0,02	0,91	03380203
254	0,12	175	0,07	0,01	1,14	03380254
305	0,12	210	0,05	0,01	1,36	03380305
350	0,12	245	0,04	0,01	1,56	03380350
407	0,12	280	0,03	0,01	2,36	03380407