


FLEXADUX® Hyp T EL CL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive

- Applications** paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, venting
- Structure** coated fabrics / Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), clip profile / multi-layer
- Temperature** -40°C up to 175°C, short term up to 190°C
- Properties** light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive ($R \leq 10^3 \text{ Ohm}$)
- Norms** TRBS 2153, ATEX 2014/34/EU



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,50	30	0,90	0,44	0,50	53319050
60	0,50	36	0,78	0,31	0,60	53319060
80	0,50	48	0,61	0,17	0,80	53319080
83	0,50	50	0,58	0,17	0,91	53319083
102	0,50	60	0,51	0,11	1,00	53319102
112	0,50	66	0,48	0,09	1,10	53319112
120	0,50	72	0,36	0,08	1,10	53319120
127	0,50	75	0,33	0,07	1,20	53319127
140	0,50	84	0,25	0,06	1,25	53319140
152	0,50	90	0,22	0,05	1,30	53319152
160	0,50	96	0,21	0,04	1,30	53319160
180	0,50	108	0,17	0,04	1,40	53319180
203	0,50	120	0,15	0,03	1,60	53319203
254	0,50	175	0,10	0,02	2,10	53319254
305	0,50	210	0,07	0,01	2,40	53319305
407	0,50	280	0,05	0,01	3,80	53319407
508	0,50	400	0,04	0,01	4,75	53319508