

# FLEXADUX® HT 650 CL

Highly flexible clip hose for temperatures up to +650°C

- Applications** exhaust gas extraction, extraction systems, high temperature applications, automotive engineering, automation technology & robotics
- Structure** coated fabrics / silicone coated glass fabric, grey / silver grey (similar RAL 7001), clip profile / multi-layer
- Temperature** -60°C up to 650°C
- Properties** excellent flexibility, excellent temperature resistance, compressible, with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,75	30	0,44	0,59	04200050
60	0,75	36	0,31	0,99	04200060
65	0,75	39	0,26	1,45	53313065
70	0,75	42	0,23	1,50	53313070
76	0,75	45	0,20	1,25	04200076
80	0,75	48	0,17	1,32	04200080
102	0,75	60	0,11	0,86	04200102
112	0,75	66	0,09	1,15	04200112
120	0,75	72	0,08	1,24	04200120
127	0,75	75	0,07	1,31	04200127
140	0,75	84	0,06	2,15	53313140
152	0,75	90	0,05	1,57	04200152
160	0,75	96	0,04	1,65	04200160
180	0,75	108	0,04	2,80	53313180
203	0,75	120	0,03	2,09	04200203
254	0,75	175	0,02	2,60	04200254
305	0,75	210	0,01	3,14	04200305
407	0,75	280	0,01	4,18	04200407
508	0,75	400	0,01	5,22	04200508