

FLEXADUX® Hyp CL

Very light weight and highly flexible spiral hose made of Hypalon

- Applications** exhaust gas extraction, extraction systems, extractions arms, steam extraction, venting
- Structure** coated fabrics / Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), clip profile / single-layer
- Temperature** -40°C up to 175°C
- Properties** very good flexibility, very good temperature resistance, very good chemical resistance, with external abrasion protection spiral, compressible
- Optional**
 - 2-ply, with PTFE foil inside
 - with stainless steel clip profile
 - with abrasion protection profile



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,40	30	0,85	0,40	0,42	03205050
60	0,40	36	0,78	0,28	0,50	03205060
76	0,40	45	0,60	0,17	0,62	03205076
80	0,40	48	0,58	0,16	0,65	03205080
102	0,40	60	0,50	0,10	0,60	03205102
110	0,40	66	0,48	0,08	0,64	03205110
120	0,40	72	0,35	0,06	0,70	03205120
127	0,40	75	0,32	0,06	0,74	03205127
152	0,40	90	0,22	0,04	0,88	03205152
160	0,40	96	0,21	0,04	0,93	03205160
180	0,40	108	0,17	0,03	1,04	03205180
203	0,40	120	0,15	0,02	0,95	03205203
254	0,40	175	0,10	0,01	1,19	03205254
305	0,40	210	0,07	0,01	1,42	03205305
350	0,40	245	0,06	0,01	1,63	03205350
407	0,40	280	0,05	0,01	2,37	03205407
508	0,40	400	0,04	0,01	2,95	03205508