

# FLEXADUX® HT 1100 CL

Highly flexible clip hose for temperatures up to +1100°C

- Applications** exhaust gas extraction, extraction systems, high temperature applications, automotive engineering, automation technology & robotics
- Structure** coated fabrics / special coated high temperature fabric, reinforced with woven stainless steel wire, grey / silver grey (similar RAL 7001), clip profile / multi-layer
- Temperature** -50°C up to 1.100°C
- Properties** good flexibility, excellent temperature resistance, compressible, with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
80	4,00	54	0,28	1,20	53323080
90	4,00	55	0,25	1,20	53323090
102	4,00	60	0,20	1,20	53323102
112	4,00	66	0,17	1,25	53323112
120	4,00	72	0,14	1,30	53323120
127	4,00	75	0,13	1,50	53323127
152	4,00	90	0,09	1,70	53323152
160	4,00	96	0,08	1,70	53323160
180	4,00	108	0,06	2,00	53323180
203	4,00	120	0,05	2,20	53323203
254	4,00	175	0,04	3,00	53323254
305	4,00	210	0,02	3,90	53323305
407	4,00	280	0,01	5,80	53323407
508	4,00	400	0,01	7,60	53323508
600	4,00	500	0,01	9,60	53323600