


FLEXADUX® Silikon CL

Very light weight and highly flexible spiral hose made of silicone

- Applications** exhaust gas extraction, extraction systems, extractions arms, steam extraction, venting
- Structure** coated fabrics / silicone coated glass fabric, grey / silver grey (similar RAL 7001), clip profile / single-layer
- Temperature** -60°C up to 300°C
- Properties** very good flexibility, very good temperature resistance, very good chemical resistance, with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,40	30	0,85	0,32	0,45	03172050
60	0,40	36	0,68	0,22	0,53	03172060
76	0,40	45	0,47	0,14	0,66	03172076
80	0,40	48	0,43	0,13	0,70	03172080
102	0,40	60	0,30	0,08	0,65	03172102
110	0,40	66	0,25	0,07	0,70	03172110
120	0,40	72	0,22	0,06	0,77	03172120
127	0,40	75	0,21	0,05	0,81	03172127
152	0,40	90	0,16	0,04	0,96	03172152
160	0,40	96	0,14	0,03	1,01	03172160
180	0,40	108	0,12	0,02	1,14	03172180
203	0,40	120	0,10	0,02	1,06	03172203
254	0,40	175	0,07	0,01	1,32	03172254
305	0,40	210	0,05	0,01	1,58	03172305
350	0,40	245	0,04	0,01	1,82	03172350
407	0,40	280	0,03	0,01	2,59	03172407
508	0,40	400	0,02	0,01	3,23	03172508