

FLEXADUX® P 3 LF hellgrau

Medium weight and flexible spiral hose made of PVC

- Applications** waste water, roof drainage, air & cooling technology, venting, automation technology & robotics
- Structure** PVC / soft PVC, grey / silver grey (similar RAL 7001), steel wire / spring steel wire / coated / PVC
- Temperature** 0°C up to 70°C
- Properties** medium weight, smooth inside, corrugated outside, good chemical resistance, hydrolysis- & microbe resistance



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
20	1,20	30	2,40	0,85	0,27	31072020
30	1,20	45	2,20	0,80	0,40	31072030
40	1,20	60	2,10	0,60	0,51	31072040
50	1,20	75	1,90	0,40	0,63	31072050
60	1,20	90	1,60	0,35	0,75	31072060
70	1,20	105	1,30	0,30	0,87	31072070
75	1,20	110	1,20	0,30	0,93	31072075
80	1,20	120	1,20	0,30	0,99	31072080
100	1,20	150	1,00	0,25	1,28	31072100
120	1,20	180	0,85	0,25	1,53	31072120
125	1,20	185	0,75	0,20	1,59	31072125
140	1,20	200	0,60	0,18	1,97	31072140
150	1,50	225	0,50	0,18	2,11	31072150
160	1,50	240	0,40	0,16	2,24	31072160
175	1,50	260	0,35	0,16	2,45	31072175
180	1,50	270	0,30	0,15	2,52	31072180
250	1,50	375	0,20	0,12	3,92	31072250
300	1,50	450	0,15	0,10	4,68	31072300
350	1,50	525	0,10	0,09	5,43	31072350
400	1,50	600	0,10	0,08	6,19	31072400
450	1,50	675	0,08	0,06	6,94	31072450

Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
500	1,50	750	0,05	0,04	7,70	31072500