


FLEXADUX® PTFE EL CL

Highly flexible clip hose made of PTFE, electrically conductive

- Applications** paint mist extraction, paper production, extraction systems, automation technology & robotics, pharmaceutical production
- Structure** coated fabrics / PTFE coated glass fabric, black / jet black (similar RAL 9005), clip profile / single-layer
- Temperature** -150°C up to 250°C
- Properties** very good flexibility, very good temperature resistance, excellent axial compressibility, very good chemical resistance, electrically conductive ($R \leq 10^3 \text{ Ohm}$)
- Norms** ATEX 2014/34/EU, TRBS 2153/TRGS 727



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
50	0,15	30	0,85	0,32	0,39	03382050
60	0,15	36	0,68	0,22	0,47	03382060
76	0,15	45	0,47	0,14	0,58	03382076
80	0,15	48	0,43	0,12	0,60	03382080
102	0,15	60	0,30	0,08	0,55	03382102
120	0,15	72	0,22	0,06	0,64	03382120
127	0,15	75	0,21	0,05	0,64	03382127
140	0,15	84	0,16	0,04	0,75	03382140
160	0,15	96	0,14	0,03	0,85	03382160
203	0,15	120	0,10	0,02	0,94	03382203
254	0,15	175	0,07	0,01	1,18	03382254