

# FLEXADUX® P-G-EX 1

Light weight and highly flexible exhaust hose made of TPE-coated Polyester fabric

- Applications** exhaust gas extraction, extraction systems, vehicle construction, venting, high temperature applications
- Structure** coated fabrics / TPE coated polyester fabric, black / jet black (similar RAL 9005), plastic spiral / PA
- Temperature** -40°C up to 150°C, short term up to 170°C
- Properties** very good temperature resistance, very good flexibility, can be driven over, crush-resistant, good oil & petrol resistance, very good chemical resistance



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
40	0,40	80	0,65	0,35	29205040
50	0,40	85	0,50	0,42	29205050
65	0,40	100	0,35	0,64	29205065
70	0,40	105	0,20	0,69	29205070
75	0,40	105	0,15	0,73	29205075
80	0,40	160	0,12	0,78	29205080
90	0,40	175	0,12	0,87	29205090
100	0,40	190	0,10	0,89	29205100
125	0,40	250	0,08	1,12	29205125
150	0,40	300	0,06	1,33	29205150
200	0,40	400	0,04	1,75	29205200
250	0,40	500	0,02	2,17	29205250