

## FLEXADUX® Vinyl CL

Very light weight and highly flexible PVC hose clip

- Applications** asbestos removal, paint mist extraction, air & cooling technology, welding gas extraction, tent heating
- Structure** coated fabrics / PVC coated polyester fabric, grey / silver grey (similar RAL 7001), clip profile / single-layer
- Temperature** -30°C up to 80°C, short term up to 100°C
- Properties** very good flexibility, excellent axial compressibility, particularly small bending radius ( $r < d$ ), with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
60	0,25	36	0,68	0,22	1,33	03472060
76	0,25	45	0,47	0,14	1,66	03472076
80	0,25	48	0,43	0,12	1,75	03472080
102	0,25	60	0,30	0,08	1,58	03472102
127	0,25	75	0,21	0,05	1,96	03472127
152	0,25	90	0,16	0,04	2,33	03472152
160	0,25	96	0,14	0,03	2,45	03472160
180	0,25	108	0,12	0,02	2,75	03472180
203	0,25	120	0,10	0,02	2,50	03472203
254	0,25	175	0,07	0,01	3,12	03472254
305	0,25	210	0,05	0,01	3,74	03472305
508	0,25	400	0,02	0,01	8,89	03472508