


FLEXADUX® P 2 SP SE

Light weight and highly flexible spiral hose made of TPE-coated Polyester fabric

- Applications** vehicle construction, extraction systems, ventilation, air conditioning & HVAC, steam extraction
- Structure** coated fabrics / TPE coated polyester fabric, black / jet black (similar RAL 9005), steel wire / spring steel wire / not coated / copper plated
- Temperature** -40°C up to 150°C
- Properties** very good flexibility, flame-retardant, good resistance against chemicals & cleaning supplies, excellent resistance to high temperatures & fumes, good mechanical strength, very good flexibility even at low temperatures
- Norms** flame-retardant according to DIN 4102 / B1
- Optional** - with polyamide helix and abrasion protection profile



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Working Pressure (bar)	Max. Vacuum (bar)	Weight (kg/m)	Article Number
20	0,40	20	0,45	0,25	0,09	29905020
25	0,40	25	0,45	0,20	0,12	29905025
30	0,40	30	0,40	0,20	0,17	29905030
40	0,40	40	0,35	0,15	0,22	29905040
50	0,40	50	0,35	0,10	0,27	29905050
60	0,40	60	0,35	0,08	0,33	29905060
70	0,40	70	0,30	0,08	0,33	29905070
75	0,40	75	0,20	0,07	0,35	29905075
80	0,40	80	0,20	0,06	0,37	29905080
100	0,40	100	0,15	0,05	0,62	29905100
125	0,40	125	0,13	0,04	0,77	29905125
140	0,40	140	0,12	0,04	0,86	29905140
150	0,40	150	0,11	0,04	0,75	29905150
200	0,40	200	0,08	0,02	1,41	29905200
250	0,40	250	0,07	0,02	1,75	29905250
350	0,40	350	0,04	0,01	1,88	29905350
500	0,40	500	0,03	0,01	2,68	29905500